

shower valves - VUE

Introduction

The Vue concealed and Exposed Sequential showers have been developed by adopting the principles of inclusive design. As a result the Vue delivers a shower which is suitable for any user, regardless of their sight or dexterity.

Inta's Vue Showers have been designed to give you the best of both worlds, offering the ultimate balance between excellent performance and the latest designs to suit every bathroom.

- Sequential control shower valve for combined control of temperature and flow
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Single piece thermal cartridge technology
- Factory set at 43°C to prevent scalding
- Temperature stability of ± 2°C
- Fail safe on hot and cold supplies
- Operating pressure range of 0.1 to 5 bar
- WRAs approved
- TMV3 scheme approved
- Exposed and concealed models available
- Chrome finish
- Full range of kits to suit



Vue Exposed Sequential Control



Vue Concealed Sequential Control

Product Range

Description	Finish	Code No.
Vue Exposed Sequential Control	Chrome	90030CP
Vue Concealed Sequential Control	Chrome	90032CP





shower valves - **VUE**


Features


Technical Specification


Max Dynamic Inlet Pressure	5 Bar
Max Static Inlet Pressure	12 Bar
Min Inlet Pressure	0.1 Bar
Max inlet Temperature	85°C
Factory Pre-set Temperature	43°C
Inlet Connections	15mm
Outlet Connections	2 x 1/2" BSP
Min temperature differential to achieve hot or cold failsafe	10°C


System Installation

Unvented, Pressurised, Gravity and Combination Boilers











Vue Exposed Sequential Control

Vue Concealed Sequential Control

▼ Flow Rates







inspiring confidence



intatec limited Airfield Industrial Estate, Hixon Staffordshire, ST18 OPF

> T: 01889 207200 F: 01889 271172

E: sales@intatec.co.uk