atlantic

Water Heater

Point of use

O'Pro technology concentrated in a compact and user-friendly water heater

Characteristics


- O'pro technology-Exclusive passive electronic anti-corrosion system to permanently combat rust
- Diamond-quality enamel
- Copper sheathed flange heating element
- Magnesium anode for optimum protection of the tank against corrosion
- Optimised inlet diffuser for the best use of the quantity of hot water
- Compact size water heaters Safety relief valve provided
- CFC-free high density polyurethane foam insulation

2 YEAR WARRANTY

DIAMOND-QUALITY ENAMEL


FAST °C HEATING

NEW FRENCH DESIGN



earthridge aftersales service


O'PRO Ohmic protection





Point of use range

Specifications					
Capacity (L)	Output (W)	Voltage (V~)	Heat-up time at 60°C (Δt=20°C)	Heat-up time at 60°C (Δt=50°C)	Energy comsumption (kWh/24h at 65°C)
10 above sink	1600	230(220/240)	10	24	0.48
15 compact above sink	1600		14	35	0.58
30	2000		23	57	0.76
50	2000		38	96	1.13
10 under sink	2000		8	19	0.63
15 compact under sink	2000		11	28	0.66




Earthridge International Ltd
Wholesale Distributors
Dowdstown, Maynooth, Co.Kildare.
Ph. 01-6286711 - Fx: 01-6286509 - email: sales@earthridge.ie


www.earthridge.ie

INSTALLATION OF COMMERCIAL UNVENTED UNDERSINK WATER HEATERS


For inlet water pressure up to 4.1 bar (with no additional kits used)



For inlet water pressure up to 4.1 bar where expansion back down the mains is not possible



For inlet water pressure above 4.1 bar



Earthridge International Ltd
Wholesale Distributors
Dowdstown, Maynooth, Co.Kildare.
Ph. 01-6286711 - Fx: 01-6286509 - email: sales@earthridge.ie

These Units Are Also Available As Oversink

Note Expansion vessel Not supplied

www.earthridge.ie