## + Fluidmaster Technical Specification Data Sheet

Fluidmaster GB Ltd Twyford Road Rotherwas Industrial Estate Hereford HR2 6JR

Part Number: PRO45B

Product Description: PRO Bottom Entry Fill Valve

WRAS Approval: 1609080

Applied Standard(s):

Material(s): ABS, Brass, POM, Rubber, Stainless Steel

Approx. Weight (kg): 0.380

Product Dimensions: See Specifications

Packaging: Boxed

Product Type: Bottom Entry Float Valve

Product Details:

- Adjustable height from 230mm to 355mm (9" to 14").
- Heavy Duty Brass Shank
- Proprietary pilot technology provides consistent water level at various pressures.
- Wide range of adjustability and valve options for most applications.
- Easy to install
- Proven and reliable quality
- Ultra Quiet
- Long Life Performance
- Fast Refill
- Minimal Water Hammer
- Standard operating pressure: 0.2 Bar (2.6 psi) 15.85 Bar (230 psi).
- Water level range: 4.0" (102mm) lowest, 11.5" (292 mm) highest
- Critical Level marking: 2" (50mm) from the top
- Recommended torque range: 6Nm to 10Nm (Approx. hand tight plus 1/2 to 3/4 turn)
- Footprint: 97 mm x 72 mm.

For further information about Fluidmaster products please go to: <a href="https://www.fluidmaster.com/united-kingdom-products/">https://www.fluidmaster.com/united-kingdom-products/</a>





Installation Notes:

See installation instructions for full detail

End Of Life Data:

Please recycle all components in accordance with local guidelines/facilities.

Product Warranty: 12 Months