





Qty.	Description
1	<p>SSP-3.0 B</p>  <p>Note! Product picture may differ from actual product</p> <p>Product No.: 98284254</p> <p>Grundfos SSP-3.0 B is a premium brass shower pump with positive head and 1 impeller, designed and manufactured to the highest standards.</p> <p>The shower pump is continuously rated as a regenerative pump making it equipped to overcome air pockets and ideal where the plumbing route includes multiple bends and elbows.</p> <p>This shower pump ensures high performance, long durability and is suitable for domestic, commercial or light industrial use to boost shower pressure up to 4 bar.</p> <p>The shower pump is used for boosting either hot or cold water to single showers, multiple showers or whole house boosting where the outlets are below the cold-water tank.</p> <p>The shower pump is characterized as heavy-duty and it relies upon brass impellers and machined brass stampings for improved durability and high performance.</p> <p>The pump is supplied with a stainless steel, flexible and braided connection hose making it resistant to corrosion. Anti-vibration feet and long-life silicon carbide seals ensure that the operating noise is held at a minimum. The shower pump has built-in thermal protection, which immediately stops the pump motor if it overheats. The shower pump is a WRAS approved product and as such the whole product has undergone and passed extensive mechanical and water quality testing. Additionally, this pump is a regenerative pump making it equipped to overcome air pockets.</p> <ul style="list-style-type: none"> - Brass impellers and housing for high performance and improved durability. - Integrated thermal protection - Regenerative impeller design to overcome air pockets - Low speed and quiet induction motor for longer durability - Continuously rated regenerative pump (in UK is used) - Long life carbide seals - Stainless steel flexible connection hose - Anti-vibration feet for minimum operating noise - WRAS approved product <p>Controls:</p> <p>Flow switch (Yes/No): Y</p> <p>Pressure switch Yes/No: Y</p> <p>Liquid:</p> <p>Pumped liquid: Water</p> <p>Liquid temperature range: 5 .. 60 °C</p> <p>Selected liquid temperature: 20 °C</p> <p>Density: 998.2 kg/m³</p> <p>Technical:</p> <p>Rated flow: 0.6 m³/h</p> <p>Rated head: 20.1 m</p> <p>Code for shaft seal: GBQP</p> <p>Approvals: CE,WRAS</p> <p>Approvals for drinking water: WRAS</p> <p>Curve tolerance: ISO9906:2012 3B</p> <p>Materials:</p> <p>Pump housing: Brass</p> <p>Impeller: Brass</p>

Qty.	Description
1	<p>Installation:</p> <p>Range of ambient temperature: 0 .. 40 °C</p> <p>Maximum operating pressure: 6 bar</p> <p>Type of inlet connection: G</p> <p>Type of outlet connection: G</p> <p>Size of inlet connection: 3/4 inch</p> <p>Size of outlet connection: 3/4 inch</p> <p>Pressure rating for connection: PN 6</p> <p>Electrical data:</p> <p>Motor type: INDUCTION</p> <p>P1 max.: 410 W</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 230 V</p> <p>Rated current: 1.8 A</p> <p>Capacitor size - run: 10 µF/450 V</p> <p>Enclosure class (IEC 34-5): X2</p> <p>Insulation class (IEC 85): F</p> <p>Built-in motor protection: YES</p> <p>Length of cable: 1.5 m</p> <p>Type of cable plug: NO</p> <p>Others:</p> <p>Net weight: 6.1 kg</p> <p>Gross weight: 6.9 kg</p> <p>Shipping volume: 0.02 m³</p> <p>Country of origin: GB</p> <p>Custom tariff no.: 84137081</p>


98284254 SSP-3.0 B GBQP 50 Hz



Description	Value
General information:	
Product name:	SSP-3.0 B GBQP
Product No:	98284254
EAN number:	5700311402504
Technical:	
Rated flow:	0.6 m³/h
Rated head:	20.1 m
Maximum head:	30 m
Code for shaft seal:	GBQP
Approvals:	CE, WRAS
Approvals for drinking water:	WRAS
Curve tolerance:	ISO9906:2012 3B
Model:	A
Materials:	
Pump housing:	Brass
Impeller:	Brass
Installation:	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	6 bar
Type of inlet connection:	G
Type of outlet connection:	G
Size of inlet connection:	3/4 inch
Size of outlet connection:	3/4 inch
Pressure rating for connection:	PN 6
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	5 .. 60 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	INDUCTION
P1 max.:	410 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	1.8 A
Capacitor size - run:	10 µF/450 V
Enclosure class (IEC 34-5):	X2
Insulation class (IEC 85):	F
Built-in motor protection:	YES
Length of cable:	1.5 m
Type of cable plug:	NO
Controls:	
Flow switch (Yes/No):	Y
Pressure switch Yes/No:	Y
Others:	
Net weight:	6.1 kg
Gross weight:	6.9 kg
Shipping volume:	0.02 m³
Country of origin:	GB
Custom tariff no.:	84137081



98284254 SSP-3.0 B GBQP 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.