





Qty.	Description
1	<p><b>SSN-3.0 B</b></p>  <p><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: <a href="#">98284260</a></p> <p>Grundfos SSN-3.0 B is a premium brass shower pump with universal head and 1 impeller, designed and manufactured to the highest standards.</p> <p>The shower pump is continuously rated as a regenerative pump making it equipped to overcome air pockets and ideal where the plumbing route includes multiple bends and elbows.</p> <p>This shower pump ensures high performance, long durability and is suitable for domestic, commercial or light industrial use to boost shower pressure up to 4 bar.</p> <p>The shower pump is used for boosting either hot or cold water to single showers, multiple showers or whole house boosting where the outlets are above or below the cold-water tank.</p> <p>The shower pump is characterized as heavy-duty and it relies upon brass impellers and machined brass stampings for improved durability and high performance.</p> <p>The pump is supplied with a stainless steel, flexible and braided connection hose making it resistant to corrosion. Anti-vibration feet and long-life silicon carbide seals ensure that the operating noise is held at a minimum. The shower pump has built-in thermal protection, which immediately stops the pump motor if it overheats. The shower pump is a WRAS approved product and as such the whole product has undergone and passed extensive mechanical and water quality testing. Additionally, this pump is a regenerative pump making it equipped to overcome air pockets.</p> <ul style="list-style-type: none"> <li>- Brass impellers and housing for high performance and improved durability.</li> <li>- Integrated thermal protection</li> <li>- Regenerative impeller design to overcome air pockets</li> <li>- Low speed and quiet induction motor for longer durability</li> <li>- Continuously rated regenerative pump (in UK is used)</li> <li>- Long life carbide seals</li> <li>- Stainless steel flexible connection hose</li> <li>- Anti-vibration feet for minimum operating noise</li> <li>- WRAS approved product</li> </ul> <p>Controls:</p> <p>Flow switch (Yes/No): Y</p> <p>Pressure switch Yes/No: N</p> <p>Liquid:</p> <p>Pumped liquid: Water</p> <p>Liquid temperature range: 5 .. 60 °C</p> <p>Selected liquid temperature: 20 °C</p> <p>Density: 998.2 kg/m<sup>3</sup></p> <p>Technical:</p> <p>Rated flow: 0.6 m<sup>3</sup>/h</p> <p>Rated head: 20.1 m</p> <p>Code for shaft seal: GBQP</p> <p>Approvals: CE,WRAS</p> <p>Approvals for drinking water: WRAS</p> <p>Curve tolerance: ISO9906:2012 3B</p> <p>Materials:</p> <p>Pump housing: Brass</p> <p>Impeller: Brass</p> <p>Installation:</p>

Qty.	Description
1	<p> Range of ambient temperature: 0 .. 40 °C  Maximum operating pressure: 6 bar  Type of inlet connection: G  Type of outlet connection: G  Size of inlet connection: 3/4 inch  Size of outlet connection: 3/4 inch  Pressure rating for connection: PN 6 </p> <p> Electrical data:  Motor type: INDUCTION  P1 max.: 410 W  Mains frequency: 50 Hz  Rated voltage: 1 x 230 V  Rated current: 1.8 A  Capacitor size - run: 10 µF/450 V  Enclosure class (IEC 34-5): X2  Insulation class (IEC 85): F  Built-in motor protection: YES  Length of cable: 1.5 m  Type of cable plug: NO </p> <p> Others:  Net weight: 6.8 kg  Gross weight: 8.3 kg  Shipping volume: 0.035 m³  Country of origin: GB  Custom tariff no.: 84137081 </p>


98284260 SSN-3.0 B GBQP 50 Hz



Description	Value
<b>General information:</b>	
Product name:	SSN-3.0 B GBQP
Product No:	98284260
EAN number:	5700311402580
<b>Technical:</b>	
Rated flow:	0.6 m³/h
Rated head:	20.1 m
Maximum head:	30 m
Code for shaft seal:	GBQP
Approvals:	CE, WRAS
Approvals for drinking water:	WRAS
Curve tolerance:	ISO9906:2012 3B
Model:	A
<b>Materials:</b>	
Pump housing:	Brass
Impeller:	Brass
<b>Installation:</b>	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	6 bar
Type of inlet connection:	G
Type of outlet connection:	G
Size of inlet connection:	3/4 inch
Size of outlet connection:	3/4 inch
Pressure rating for connection:	PN 6
<b>Liquid:</b>	
Pumped liquid:	Water
Liquid temperature range:	5 .. 60 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
<b>Electrical data:</b>	
Motor type:	INDUCTION
P1 max.:	410 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	1.8 A
Capacitor size - run:	10 µF/450 V
Enclosure class (IEC 34-5):	X2
Insulation class (IEC 85):	F
Built-in motor protection:	YES
Length of cable:	1.5 m
Type of cable plug:	NO
<b>Controls:</b>	
Flow switch (Yes/No):	Y
Pressure switch Yes/No:	N
<b>Others:</b>	
Net weight:	6.8 kg
Gross weight:	8.3 kg
Shipping volume:	0.035 m³
Country of origin:	GB
Custom tariff no.:	84137081



# 98284260 SSN-3.0 B GBQP 50 Hz



Note! All units are in [mm] unless others are stated.  
Disclaimer: This simplified dimensional drawing does not show all details.